



STANDARD MARINE AXIAL FANS

Standard Fans

Delta “T” Systems’ Standard Axial Ventilation Fans are specifically designed and built for the rigors of the marine environment, not adapted from other industries. Available in standard and custom sizes to fit your needs.



Design & Construction

Flanged rolled steel housings are epoxy coated to provide excellent durability and corrosion resistance. Major assembly hardware is corrosion resistant stainless steel for long life.

Motor

High efficiency NEMA Premium three phase or single phase direct drive motors are utilized to provide quiet continuous duty service. Available with “CE” Classification, 50 or 60 HZ.

Fan Hubs & Blades

Corrosion resistant aluminum hubs are secured directly to the motor shaft using multiple locking methods for enhanced safety and reliability. Fan blades are non-corrosive polypropylene composite.

Finish

Durable epoxy coated paint finish.

	OD	Bolt Circle	ID	Length	Bolt Holes
12 in. 304.8 mm	14 1/16 in. 357.2 mm	13 1/8 in. 333.4 mm	12 in. 304.8 mm	20 in. 508.0 mm	8 x 7/16 in. 8 x 11.1 mm
15 in. 381.0 mm	17 1/16 in. 433.4 mm	16 1/8 in. 409.6 mm	15 in. 381.0 mm	20 in. 508.0 mm	8 x 7/16 in. 8 x 11.1 mm
18 in. 457.2 mm	20 1/16 in. 509.6 mm	19 1/8 in. 485.8 mm	18 in. 457.2 mm	20 in. 508.0 mm	8 x 7/16 in. 8 x 11.1 mm
24 in. 609.6 mm	26 11/16 in. 677.9 mm	25 13/16 in. 655.6 mm	24 in. 609.6 mm	21 in. 533.4 mm	8 x 7/16 in. 8 x 11.1 mm
30 in. 762 mm	32 11/16 in. 830.3 mm	31 3/4 in. 806.5 mm	30 in. 762.0 mm	22 in. 558.8 mm	8 x 7/16 in. 8 x 11.1 mm
36 in. 914.4 mm	39 1/4 in. 997.0 mm	37 7/8 in. 962.0 mm	36 in. 914.4 mm	28 in. 711.2 mm	8 x 7/16 in. 8 x 11.1 mm
42 in. 1066.8 mm	45 1/4 in. 1149.4 mm	43 9/16 in. 1106.5 mm	42 in. 1066.8 mm	29 in. 736.6 mm	8 x 7/16 in. 8 x 11.1 mm
48 in. * 1219.2 mm	51 in. 1295.4 mm	49 5/8 in. 1260.5 mm	48 in. 1219.2 mm	31 in. 787.4 mm	8 x 7/16 in. 8 x 11.1 mm

* Special Order Only